

# Model: IM-IR6810H

**Camera Housing With IR 50m, Heater, Blower, PoE**

## Features

- Die-Cast Aluminum Camera Housing
- Includes mounting bracket (die-cast aluminum construction)
- Dual glass construction
- Tempered Glass Window Viewing
- Designed for indoor and outdoor applications
- Side opening (Locked with stainless steel nuts)
- High impact resistance
- Built in heater and blower (optional).
- Built in IR illuminator with distance up to 50 m
- Cable entry glands and mounting holes on bottom of housing
- Power input by PoE (Support camera, IR, heater and blower)
- Compatible with both PoE and Non-PoE Camera



### Technical Specification

Model	IM-IR6810H
Application	Indoor and outdoor camera housing / side opening
Material	Die-cast aluminum
Color (Housing and mounting bracket)	White
Protection Rating	IP66, IK10
Power input	IEEE 802.3af/at PoE (30W)
Cover consumption	Heater : 4.2W Blower : 1.8W IR :Eds : 4W
Network Interface	RJ45
Camera mounting	Removeable camera metal sled
Heater	15 °C On, 25 °C Off
Blower	35 °C On, 25 °C Off
Operating Temperature	-30 °C to 50 °C
Illumination Distance	50 m
LED lifetime	20,000 hours
Light On/Off	On when illumination is lower 4 lux
Standard	CE, CE (EN 60529), FCC

\* ข้อมูลเฉพาะและสินค้าอาจเปลี่ยนแปลงได้โดยไม่ต้องแจ้งให้ทราบล่วงหน้าสำหรับการปรับปรุงคุณภาพอย่างต่อเนื่อง

จัดจำหน่ายโดย

**บริษัท ไอมีเดีย อินโนเวชั่น จำกัด**

189/10 หมู่ 12 ต.บางแก้ว อ.บางพลี จ.สมุทรปราการ 10540

Mobile: 092-3939-156 Tel. 0-2312-0515 Fax. 0-2312-0516

E-mail: sale@imediathailand.com Website: www.imediathailand.com